



# COLORADO MILL EQUIPMENT ECO-CF3 PELLET COOLER

The CF3 pellet cooler has a capacity of 1 to 3 tons per hour, depending on pellet size, density, temperature and composition. It is commonly used to cool pellets from 1/32" to 3/8" diameter, from up to 250°F to within 10° of ambient.

## FEATURES:

- Variable swing discharge grid (1000mm x 1000mm)
- Rotary valve at inlet
- Various configurations available
- Easy maintenance, heavy-duty construction
- Clear view chamber door design
- Optimal efficiency counterflow
- All NEMA frame motors



## OPTIONS:

- 7½HP Blower
- Cyclone with stand
- Airlock valve with sight glass
- Single-deck pellet screener
- Duct work

# CME

## ECO-CF3 PELLET COOLER

The ECO CF-3 is commonly used to cool the following pellets:

- Animal Bedding
- Animal Feed
- Biomass
- Cardboard
- Chemicals
- Fertilizer
- Hops
- Paper
- Plastic
- Recycling
- Wood Pellets



### SPECIFICATIONS:

- **Model:** ECO-CF3
- **Voltage:** 230/460VAC
- **Discharge Grid Motor:** 1HP (.75KW)
- **Screener Motor:** 1/4HP (.2KW)
- **Blower Motor:** 7.5HP (5.6KW)
- **Airlock Motor:** 1HP (.75KW)
- **Rotary Valve Motor:** 1HP (.75KW)